

ALUPROP

Take advantage of our best prop, **high load-bearing capacity**, and **lightweight** aluminum shoring post



Contact us today for more details at info@ulmaconstruction.ca

IN STOCK FOR IMMEDIATE DELIVERY

FINANCING AVAILABLE


UP to 40% DISCOUNT

ON PURCHASE OF NEW EQUIPMENT

MAIN FEATURES

- · Lightweight Aluminum prop.
- **High load capacity**: Up to 100 kN.
- Certified prop according to EN 16031.
- Perforated wing nut facilitates prop removal.
- Self-cleaning thread eliminates concrete on the inner tube
- Possibility to gain height by placing prop on prop connected with ALUPROP clamp or with bolts. Suits assembly of **high shorings**.
- Easy and quick length adjustment.
- **Safety:** Shoring structure can be assembled in horizontal position on the ground. Subsequent lifting and placing with crane, enables ergonomic and safe working conditions for workers.





I ALUPROP RANGE

Up to 19.7 ft with a single prop

- **ALUPROP** 1.65-2.8 (2220010)
- **ALUPROP** 2.2-3.7 (2220020)
- **ALUPROP** 3.3-4.8 (2220030)
- **ALUPROP** 4.5-6.0 (2220040)
- SUPPLEMENT 1 m (2220055)



When you buy from **ULMA**, you are buying **quality** products for years to come with **exceptional service** from a global industry leader.







www.ulmaconstruction.ca